



CSG 74

| CSG |

TOP CLASS DISPLAY

At first sight it may look like a traditional freezer for ice cream, but furthermore we can offer very high quality and reliability. This means that the customer can just plug it in and forget about it for years to come - it will simply do its job.

FEATURES

- Low service costs
- Perfect view to the products
- Custom made design
- Long life
- Available in all climate classes
- Graphics (option)
- Scoope (option)
- 8 different freezers available
- Accessories including baskets - see page 64



CSG 18



CSG 22



CSG 35




CSG 45



CSG 53



CSG 61



	CSG 18	CSG 22	CSG 35	CSG 45	CSG 53	CSG 61	CSG 73	CSG 74
Climate class 4	4	4	4	4	4	4	4	4
Ambient temperature range	+16 to +30	+16 to +30	+16 to +30	+16 to +30	+16 to +30	+16 to +30	+16 to +30	+16 to +30
Climate class 4+	7 (=4+)	7 (=4+)	7 (=4+)	7 (=4+)	7 (=4+)	7 (=4+)	7 (=4+)	7 (=4+)
Ambient temperature range	+16 to +35	+16 to +35	+16 to +35	+16 to +35	+16 to +35	+16 to +35	+16 to +35	+16 to +35
Gross volume, litres	170	217	349	450	530	611	700	677
Net volume, litres	146	188	304	393	441	509	622	527
Temperature range inside unit	-14 to -23	-14 to -23	-14 to -23	-14 to -23	-14 to -23	-14 to -23	-14 to -23	-14 to -23
Refrigerants available: R134a/R290/ R404a/R600a	Yes	Yes	Yes	Yes	Yes	Yes	Yes	yes
Energy cons. / 24 h[R 134a]kwh at 30 deg C, 60 % running time	2,7	2,7	3,2	4,2	5,6	5,6	6,7	6,7
Input power for R134a (watt)	141	141	166	226	290	290	350	350

DIMENSIONS								
External dimensions (wxdxh)	628*628*916	724*654*916	1054*654*916	1304*654*916	1504*654*916	1704*654*916	1804*694*916	1754*744*878
Internal dimensions (wxdxh)	510*510*750	606*536*750	936*536*750	1186*536*750	1386*536*750	1586*536*750	1686*576*750	1636*626*692
Dimension A	628	724	1054	1304	1504	1704	1804	1754
Dimension B	628	654	654	654	654	654	654	744
Dimension C	916	916	916	916	916	916	916	878
Dimension D	780	780	780	780	780	780	780	742
Dimension E	510	606	936	1186	1386	1586	1686	1636
Dimension F	310	406	736	986	1186	1386	1486	1436
Dimension G	510	510	510	510	510	510	510	626
Dimension H	750	750	750	750	750	750	750	692
Dimension J	500	500	500	500	500	500	500	442
Dimension L	846	846	846	846	846	846	846	808
Insulation (mm)	60	60	60	60	60	60	60	60
ACCESSORIES								
Dividers	Optional	Optional	Optional	Optional	Optional	Optional	Optional	optional
Max. number of baskets	0	2	3	4	4	4	6	n/a
Castors	Incl.	Incl.	Incl.	Incl.	Incl.	Incl.	Incl.	incl.
Castors w. brakes	Optional	Optional	Optional	Optional	Optional	Optional	Optional	optional
Lock	Optional	Optional	Optional	Optional	Optional	Optional	Optional	optional
Thermometer	Optional	Optional	Optional	Optional	Optional	Optional	Optional	optional
Internal light	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
OTHER DATA								
Outer cabinet	White	White	White	White	White	White	White	white
Inner cabinet	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium	aluminium
Graphics	Optional	Optional	Optional	Optional	Optional	Optional	Optional	optional
Type of cooling	Static	Static	Static	Static	Static	Static	Static	static
Type of defrost	Manual	Manual	Manual	Manual	Manual	Manual	Manual	manual
Power*	220-240V/50hz	220-240V/50hz	220-240V/50hz	220-240V/50hz	220-240V/50hz	220-240V/50hz	220-240V/50hz	220-240V/50hz
Power 110volt / 60 hz	Optional	Optional	Optional	Optional	Optional	Optional	Optional	1/o
Thermostat	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	mechanical
Net weight, kg	45	47	54	64	67	77	85	85
Gross weight, kg	51	50	58	68	71	82	89	89
SHIPPING								
20' cont. Capacity	48	42	30	24	20	18	14	14
40' cont. Capacity	102	90	64	50	46	40	30	28
40' HC cont. Capacity	138	126	88	62	61	52	42	41
Standard Trailer capacity	120	102	74	60	52	44	42	32